

Performance & Feature Reference



Model Number	GBL 10	N27921 (Truck Unloading Auger)	GBU 10
Operating Weight	4080 pounds	4540 pounds	5760 pounds
Operating Dimensions			
Length	170 in.	362 in. / w GBL	255 in.
Width	150 in.	290 in.	269 in.
Height	129 in.	129 in.	209 in.
Storage/Travel Dimensions			
Length	170 in.	362 in. / w GBL	263 in.
Width	150 in.	150 in.	103 in.
Height	130 in.	130 in.	107 in.
Width	(136 in with travel kit)		
Hopper Dimensions			
GL-10 Loader	100 in. X 104 in.		
GL-10 Truck Auger		40 in. X 72 in. X 12 in.	
GL-10 Truck Auger w/extension		40 in. X 72 in. X 19 in.	
PTO			
RPM	540	1000	540
Horsepower	50	120	50
Shaft Size / Type	6-B Spline	1 3/8 or 1 3/4	6-B Spline
PTO Driveline Type	Walterscheid W2400	Walterscheid W2400	Walterscheid W2400
Hydraulics			
GPM (required)	6	6	6
PSI (required)	2,000	2,000	2,000
Connector Type	Quick Couplers	Quick Couplers	Quick Couplers
Auger Sizes			
Primary Auger	17 in. / 385 RPM	13 in. / 540 RPM	
Discharge Auger			17 in. /331 RPM
Cross Auger			10 in. /356 RPM
Secondary Auger		14 in. / 540 RPM	Optional 5 in. Auxiliary
Twin Hopper Auger		7 In. /750RPM	
Wheels / Tires			
Wheel Size	33 in.	15 in.	31 in.
Tire Size	12.5L-15	16-6.5	11L-15
Tire Type	SureGrip Traction	Foam Filled Traction Tire	Implement
Operational Braking System	Hydraulic Disc		
Performance			
Transfer Capacity	26,000 Bushels / Hr.	11,900 Bushels / Hr.	8,500 Bushels / Hr.
Bag Handling Capacity			
Diameter	10 Foot Bags		9 foot or 10 Foot Bags
Max. Length	300 Feet		300 Feet